

Quick Manual for EDGE-100M PCMCIA card

Thank you for using this product for your application.

Hardware

1. Description

- a. ANT (shown on housing): Antenna for GSM network
- b. SIM : It is for inserting SIM card.
- c. Earphone : It is for plugging earphone cable for voice communication.
- d. NET: When unit connects to cellular service station, LED will start blinking.
- e. PWR: When power is provided. This card needs 5VDC power.



(More information on the other side)

Quick Guide for EDGE PCMCIA modem installation

- 1. Please insert CD to CD drive, Software (Mobile Phone Tool) will install automatically.
- 2. If you want to use this card without software, please use DTE speed 460800 to communicate with this card.

Software Installation Manual for EDGE-100M modem

Please do not insert EDGE-100M card before installing software.

1. Please insert BVRP CD into your CD ROM drive. Software will auto-run by itself.

2. Please click “Next” and select “Install the application”

3. Then Software set up is completed and ask which hardware you want to install.

Please have your SIM card PIN code (security password) disabled. Then insert SIM card into SIM card holder.

But do not insert PCMCIA card into Notebook or PC yet.

After all installation is completed, you can set SIM pin code again.

Please select “PCMCIA” as a device to be installed.

Software will install PCMCIA card automatically, then ask to plug in PCMCIA card.

4. Please insert PCMCIA card with SIM card inserted. Software will auto install driver.

5. After installing PCMCIA card, BVRP will start to initialize PCMCIA card. Installation is completed.

Trouble-shooting

After launching Mobile Phone Tool, You also can click on “MENU” , “View” , “Modem Exchange”, to see all commands issued to modem and how modem response to software.

When you close this software, please make sure you wait for software to release modem. Otherwise it may cause some error. If it happened, you may need to use Ctrl+Alt+Del to stop the operation.